## (19) World Intellectual Property Organization International Bureau



## - 1 (111) (111) (111) (111) (111) (111) (111) (111) (111) (111) (111) (111) (111) (111) (111) (111) (111) (111)

(43) International Publication Date 22 January 2004 (22.01.2004)

**PCT** 

(10) International Publication Number WO 2004/007836 A1

- (51) International Patent Classification7: B01J 37/34
- D21F 3/08,
- (74) Agent: TAMPEREEN PATENTTITOIMISTO OY; Hermiankatu 12 B, FIN-33720 Tampere (FI).
- (21) International Application Number:

PCT/FI2003/000569

- (22) International Filing Date:
- 16 July 2003 (16.07.2003)
- (25) Filing Language:

Finnish

(26) Publication Language:

English

(30) Priority Data:


20021390

16 July 2002 (16.07.2002) FI

- (71) Applicant (for all designated States except US): MILLI-DYNE OY [FI/FI]; Hermiankatu 8 D, FIN-33720 Tampere (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KNUUTTILA, Jari [FI/FI]; Tapionkatu 23 E 83, FIN-33500 Tampere (FI). SORSA, Petri [FI/FI]; Piiriniitynkatu 21 E 18, FIN-33340 Tampere (FI).
- (81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A METHOD FOR CONTROLLING THE PROPERTIES OF A SURFACE



(57) Abstract: In a method for adjusting the properties of a surface in a rotating member (3) that is in contact with a continuous moving material web (W) the surface of the rotating member (3) that is in contact with the material web (W) contains photocatalytically active material, light is directed to the surface of the rotating member (3) that is in contact with the material web (W), the light having such energy that it is capable of activating the photocatalytically active material, and the activation of the photocatalytically active material causes oxidation of substances on the surface of the rotating member (3) and/or changes in the hydrophilic properties of the surface.